



TANK TRUCK PETROLEUM HOSE W.P. 150 PSI



Our Tank Truck Petroleum Hose is engineered for reliability in oil and fuel applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Oil & Fuel resistant conductive black NBR








Reinforcement: High-tensile synthetic cord with steel wire helix antistatic copper wire

Cover: Oil, petroleum products, weather and ozone resistant, smooth, cloth impression black NBR

Temperature Range: -30°C to +70°C (-22°F to +158°F)

Applications:

Ideal for use tank trucks and transfer of petroleum products with aromatic content up to %50

| |  |  | |  |  |  | |  |  |
|----------------|---|---|-----|---|---|---|--------|---|---|
| | ID | OD | | WP | BP | W | | BR | L |
| code | inch | inch | mm | psi | psi | gr/mt | lbs/ft | mm | ft |
| MO-010-025-ATT | 1 | 1,37 | 35 | 150 | 450 | 770 | 0,52 | 150 | 100 |
| MO-010-032-ATT | 1 1/4 | 1,65 | 42 | 150 | 450 | 925 | 0,62 | 200 | 100 |
| MO-010-038-ATT | 1 1/2 | 1,93 | 49 | 150 | 450 | 1100 | 0,74 | 250 | 100 |
| MO-010-051-ATT | 2 | 2,44 | 62 | 150 | 450 | 1700 | 1,14 | 300 | 100 |
| MO-010-063-ATT | 2 1/2 | 2,95 | 75 | 150 | 450 | 2200 | 1,48 | 360 | 100 |
| MO-010-076-ATT | 3 | 3,5 | 89 | 150 | 450 | 2950 | 1,98 | 460 | 100 |
| MO-010-102-ATT | 4 | 4,56 | 116 | 150 | 450 | 4475 | 3,01 | 600 | 100 |
| MO-010-127-ATT | 5 | 5,63 | 143 | 150 | 450 | 5850 | 3,93 | 750 | 100 |
| MO-010-152-ATT | 6 | 6,7 | 170 | 150 | 450 | 8300 | 5,57 | 900 | 100 |
| MO-010-203-ATT | 8 | 8,78 | 223 | 150 | 450 | 12150 | 8,18 | 1200 | 100 |

