

# CABLE COOLING HOSE 300 PSI



Our CBL COOL is engineered for resistant to open flame and molten metal

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: EPDM, white, smooth and non-conductive, heat resistant







Reinforcement: High-tensile textile cords

Cover: White EPDM and non-conductive, heat resistant

Temperature Range: -40°C to +130°C (-40°F to +248°F) Cover to intermittent +1022°F

## Applications:

Suitable for non conductive cable cooling electric furnaces in steel mills industry

								
	ID	OD		WP	BP	W		L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MFG-020-013-V	1/2	0,98	25	300	900	520	0,34	100
MFG-020-019-V	3/4	1,22	31	300	900	800	0,53	100
MFG-020-025-V	1	1,50	38	300	900	940	0,63	100
MFG-020-032-V	1 1/4	1,81	46	300	900	1575	1,05	100
MFG-020-038-V	1 1/2	2,13	54	300	900	1880	1,26	100
MFG-020-051-V	2	2,64	67	300	900	2750	1,84	100
MFG-020-063-V	2 1/2	3,19	81	300	900	3300	2,21	100
MFG-020-076-V	3	3,78	96	300	900	4250	2,85	100



## CABLE COOLING HOSE W.P. 300 PSI



[www.arkhoses.com](http://www.arkhoses.com)



13201 NW Freeway, Suite 800,  
Houston, Texas, 77040

+1 832 577 2505



[info@arkhoses.com](mailto:info@arkhoses.com)