



BUNKERING SUCTION & DISCHARGE HOSE W.P. 250 PSI



Our Bunkering Suction Discharge Hose is engineered for reliability in bunkering applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.






Tube: Fuel resistant conductive black NBR.
Reinforcement: High-tensile synthetic cord with steel wire helix and double copper wires.

Cover: Petroleum, weather and ozone resistant, smooth, cloth impression black Neoprene rubber .

Temperature Range: -40°C to +95°C
(-40°F to +203°F))

Applications:

Ideal for use handling of high pressure discharge of petroleum products with aromatic content up to %50 bunkering services

									
	ID	OD		WP	BP	W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MO-017-051-AVBK	2	2,59	66	250	1000	2000	1,34	300	100
MO-017-076-AVBK	3	3,70	94	250	1000	3450	2,31	400	100
MO-017-102-AVBK	4	4,72	120	250	1000	5000	3,35	500	100
MO-017-127-AVBK	5	5,94	151	250	1000	7850	5,27	600	100
MO-017-152-AVBK	6	6,93	176	250	1000	9250	6,21	800	100
MO-017-203-AVBK	8	9,09	231	250	1000	16750	11,20	1200	50

