



CORRUGATED OILFIELD VAC HOSE W.P. 150 PSI



CORRUGATED OILFIELD VAC HOSE W.P. 300 PSI








Our Cor Oilfield Vac Hose is engineered for reliability in oilfield vacuum applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Fuel resistant conductive black NBR
Reinforcement: High-tensile synthetic cord with steel wire helix.

Cover: Petroleum, weather and ozone resistant, corrugated, cloth impression black NBR
Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Applications:

Ideal for use transfer of oilfield waste , sludge, brine water

									
	ID	OD		WP	BP	W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MO-010-038-CLF	1 1/2	1,92	49	150	450	980	0,65	300	100
MO-010-051-CLF	2	2,44	62	150	450	1400	0,94	410	100
MO-010-063-CLF	2 1/2	3	76	150	450	1830	1,22	500	100
MO-010-076-CLF	3	3,46	88	150	450	2400	1,61	600	100
MO-010-102-CLF	4	4,56	116	150	450	3700	2,48	800	100
MO-010-127-CLF	5	5,62	143	150	450	4300	2,88	1000	100
MO-010-152-CLF	6	6,61	168	150	450	5000	3,35	1200	100
MO-010-203-CLF	8	8,7	221	150	450	8250	5,54	1600	50

