



CORRUGATED OILFIELD VAC HOSE W.P. 300 PSI



CORRUGATED OILFIELD VAC HOSE W.P. 300 PSI








Our Cor Oilfield Vac Hose is engineered for reliability in oilfield vacuum applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Fuel resistant conductive black NBR
Reinforcement: High-tensile synthetic cord with steel wire helix.

Cover: Petroleum, weather and ozone resistant, corrugated, cloth impression black NBR
Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Applications:

Ideal for use transfer of oilfield waste , sludge, brine water

									
	ID	OD		WP	BP		W	BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MO-020-038-CLF	1 1/2	1,93	49	300	900	1100	0,73	300	100
MO-020-051-CLF	2	2,48	63	300	900	1500	1,00	410	100
MO-020-063-CLF	2 1/2	3	76	300	900	1875	1,25	500	100
MO-020-076-CLF	3	3,54	90	300	900	2450	1,64	600	100
MO-020-102-CLF	4	4,64	118	300	900	3775	2,53	800	100
MO-020-127-CLF	5	5,62	143	300	900	4400	2,95	1000	100
MO-020-152-CLF	6	6,69	170	300	900	6100	4,09	1200	100
MO-010-203-CLF	8	8,85	225	300	900	9750	6,55	1600	50

