



DOCK LOADING HOSE 225 PSI



Our Dock Hose is engineered for reliability in fuel applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Fuel resistant conductive black NBR.
Reinforcement: High-tensile synthetic cord with 2 steel wire helix and antistatic copper wire
Cover: Petroleum, weather, ozone and sea






water resistant, smooth, cloth impression black NBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Remarks: Corrugated version

Applications:

Ideal for use for suction and discharge of petroleum products with aromatic content up to %50 from tankers and barges bunkering services

									
	ID	OD		WP	BP	W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MO-015-102-DO	4	5,11	130	225	900	6950	4,67	500	100
MO-015-127-DO	5	6,22	158	225	900	9600	6,45	650	100
MO-015-152-DO	6	7,40	188	225	900	14250	9,57	750	100
MO-015-203-DO	8	9,52	242	225	900	19900	13,30	950	50
MO-015-254-DO	10	11,60	296	225	900	26975	18,10	1200	50

