

MARINE EXHAUST HOSE - SOFTWALL - SAEJ 2006/R1



Our Marine Exhaust Hose- Softwall - SAEJ 2006/R1 is built for marine industries.

It is designed with premium materials for resistance against abrasion, weather, and ozone, ensuring durability in demanding environments.

Tube: Smooth, black EPDM, resistant to air, water, gas and fuel mist.




Reinforcement: High-tensile synthetic cord

Cover: Black EPDM, resistant to air, water, and fuel mist.

Temperature Range: -30°C to +85°C (-22°F to +185°F)

Applications:

Ideal for use wet marine exhaust applications.

							
	ID	OD		WP	W		L
code	inch	inch	mm	psi	gr/mt	lbs/ft	ft
MO-005-013-VM	1/2	0,87	22	75	450	0,30	100
MO-005-019-VM	3/4	1,14	29	75	550	0,36	100
MO-005-022-VM	7/8	1,26	32	75	625	0,41	100
MO-005-025-VM	1	1,38	35	75	700	0,47	100
MO-005-028-VM	1 1/8	1,57	40	75	810	0,54	100
MO-005-032-VM	1 1/4	1,65	42	75	890	0,59	100
MO-005-035-VM	1 3/8	1,77	45	75	960	0,64	100
MO-005-038-VM	1 1/2	1,89	48	75	1025	0,68	100
MO-005-042-VM	1 5/8	2,01	51	75	1075	0,72	100
MO-005-045-VM	1 3/4	2,13	54	75	1190	0,79	100
MO-005-048-VM	1 7/8	2,28	58	75	1150	0,77	100
MO-005-051-VM	2	2,44	62	75	1550	1,04	100
MO-005-055-VM	2 1/8	2,60	66	75	1650	1,10	100
MO-005-057-VM	2 1/4	2,72	69	75	1750	1,17	100
MO-005-060-VM	2 3/8	2,83	72	75	1800	1,20	100
MO-005-063-VM	2 1/2	2,95	75	75	1910	1,28	100
MO-005-070-VM	2 3/4	3,23	82	75	2175	1,46	100
MO-005-076-VM	3"	3,46	88	75	2275	1,52	100
MO-005-090-VM	3 1/2"	3,98	101	75	2600	1,74	100
MO-005-102-VM	4	4,57	116	75	3900	2,62	100



MARINE EXHAUST HOSE - SOFTWALL - SAEJ 2006/R1



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com