



PETROLEUM DISCHARGE HOSE W.P. 150 PSI



PETROLEUM DISCHARGE HOSE W.P. 150 PSI



Our Petroleum Discharge Hose is engineered for reliability in fuel applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.





Tube: Fuel resistant conductive black NBR.
Reinforcement: High-tensile synthetic cord with antistatic copper wire.
Cover: Petroleum, weather and ozone resistant,

smooth, cloth impression black NBR.
Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Remarks: Upon request also available with 4:1 safety factor for offshore industry.

Applications:

Ideal for use discharge of petroleum products with aromatic content up to %50

									
	ID	OD		WP	BP		W	BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MO-010-019-V	3/4	1,18	30	150	450	550	0,36	100	100
MO-010-025-V	1	1,41	36	150	450	650	0,43	100	100
MO-010-032-V	1 1/4	1,69	43	150	450	830	0,55	100	100
MO-010-038-V	1 1/2	1,92	49	150	450	980	0,65	100	100
MO-010-051-V	2	2,48	63	150	450	1400	0,94	100	100
MO-010-063-V	2 1/2	3	76	150	450	1830	1,22	100	100
MO-010-076-V	3	3,54	90	150	450	2400	1,61	100	100
MO-010-102-V	4	4,64	118	150	450	3700	2,48	100	100
MO-010-127-V	5	5,62	143	150	450	4300	2,88	100	100
MO-010-152-V	6	6,61	168	150	450	5000	3,35	100	100
MO-010-203-V	8	8,7	221	150	450	7900	5,3	50	100

