



SAE J 517 100 R4 HOSE








Our SAE J 517 R4 Hose is engineered for reliability in fuel applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Hydraulic resistant black NBR.
Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wire.

Cover: Petroleum weather and ozone resistant, smooth, cloth impression black NBR.
Temperature Range: -30°C to +100°C (-22°F to +212°F)

Applications:

Ideal for use suction and discharge of hydraulic petroleum

									
	ID	OD		WP	BP		W	BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
HO-021-019-A	3/4	1,25	32	315	1260	770	0,51	140	100
HO-017-025-A	1	1,41	36	250	1000	880	0,59	150	100
HO-014-032-A	1 1/4	1,69	43	210	840	1200	0,80	200	100
HO-010-038-A	1 1/2	1,92	49	150	600	1530	1,02	250	100
HO-007-051-A	2	2,48	63	100	400	1910	1,28	300	100
HO-004-063-A	2 1/2	3,00	76	60	240	2620	1,76	360	100
HO-004-076-A	3	3,54	90	60	240	3150	2,11	430	100
HO-002-102-A	4	4,64	118	30	120	4200	2,82	520	100

