

MARINE FUEL FILL SUCTION & DELIVERY HOSE

ISO 7840 A1- SAE J1527/R2



Our Sanitary Hose is built for marine industries. It is designed with premium materials for resistance against abrasion, weather, and ozone, ensuring durability in demanding environments.

Tube: Smooth, black SBR, resistant to air, water, and oil mist.




Reinforcement: High-tensile synthetic cord for added strength and reliability.

Cover: Gray SBR with a cloth impression finish, providing excellent weather and ozone resistance.

Temperature Range: -30°C to +85°C
(-22°F to +185°F)

Applications:

Ideal for use in the marine industry sanitary applications.

								
	ID	OD		WP	BR	W		
code	inch	inch	mm	psi	mm	gr/mt	lbs/ft	ft
MO-010-019-AM	3/4"	1,18	30	150	60	670	0,45	100
MO-010-022-AM	7/8"	1,30	33	150	65	715	0,48	100
MO-010-025-AM	1"	1,43	36	150	75	980	0,66	100
MO-010-032-AM	1 1/4"	1,75	44	150	90	1175	0,79	100
MO-010-038-AM	1 1/2"	1,99	50	150	120	1360	0,92	100
MO-010-051-AM	2"	2,50	63	150	150	1770	1,19	100
MO-010-063-AM	2 1/2"	3,00	76	150	200	2275	1,53	100
MO-010-076-AM	3"	3,52	89	150	300	2850	1,92	100
MO-010-102-AM	4"	4,52	114	150	400	3735	2,51	100



SANITARY HOSE



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com