

# STEEL STEAM HOSE 250 PSI 210°C



Our STEAM/ST Hose is engineered for reliability in steam applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.






Tube: Seamless Steam resistant black EPDM

Reinforcement: High-tensile steel cord for added strength and durability.

Cover: Red EPDM -Steam, ozone, and weather resistant.

Temperature Range: -30°C to +210°C (-22°F to +400°F)

Remarks: Standart: BS5342/A2

|               |  |  |     |  |  |       |  |  |  |
|---------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| code          | inch                                                                               | inch                                                                               | mm  | psi                                                                                | psi                                                                                | gr/mt | lbs/ft                                                                               | mm                                                                                   | ft                                                                                   |
| MS-017-013-VR | 1/2                                                                                | 0,98                                                                               | 25  | 250                                                                                | 2500                                                                               | 525   | 0,35                                                                                 | 140                                                                                  | 100                                                                                  |
| MS-017-016-VR | 5/8                                                                                | 1,10                                                                               | 28  | 250                                                                                | 2500                                                                               | 600   | 0,40                                                                                 | 180                                                                                  | 100                                                                                  |
| MS-017-019-VR | 3/4                                                                                | 1,22                                                                               | 31  | 250                                                                                | 2500                                                                               | 700   | 0,47                                                                                 | 200                                                                                  | 100                                                                                  |
| MS-017-025-VR | 1                                                                                  | 1,49                                                                               | 38  | 250                                                                                | 2500                                                                               | 950   | 0,63                                                                                 | 260                                                                                  | 100                                                                                  |
| MS-017-032-VR | 1 1/4                                                                              | 1,81                                                                               | 46  | 250                                                                                | 2500                                                                               | 1250  | 0,83                                                                                 | 350                                                                                  | 100                                                                                  |
| MS-017-038-VR | 1 1/2                                                                              | 2,04                                                                               | 52  | 250                                                                                | 2500                                                                               | 1600  | 1,07                                                                                 | 460                                                                                  | 100                                                                                  |
| MS-017-051-VR | 2                                                                                  | 2,59                                                                               | 66  | 250                                                                                | 2500                                                                               | 2350  | 1,57                                                                                 | 600                                                                                  | 100                                                                                  |
| MS-017-063-VR | 2 1/2                                                                              | 3,26                                                                               | 83  | 250                                                                                | 2500                                                                               | 3350  | 2,25                                                                                 | 750                                                                                  | 100                                                                                  |
| MS-017-076-VR | 3                                                                                  | 3,85                                                                               | 98  | 250                                                                                | 2500                                                                               | 4300  | 2,88                                                                                 | 900                                                                                  | 100                                                                                  |
| MS-017-102-VR | 4                                                                                  | 4,88                                                                               | 124 | 250                                                                                | 2500                                                                               | 7000  | 4,70                                                                                 | 1300                                                                                 | 100                                                                                  |

 **STEAM HOSE 250 PSI**