



TANK TRUCK PETROLEUM HOSE W.P. 300 PSI








Our Tank Truck Petroleum Hose is engineered for reliability in heavy duty fuel applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Fuel resistant conductive black NBR
Reinforcement: High-tensile synthetic cord with steel wire helix antistatic copper wire

Cover: Petroleum products , weather and ozone resistant, smooth, cloth impression black NBR
Temperature Range: -30°C to +70°C (-22°F to +158°F)

Applications:

Ideal for use high pressure of tank trucks and transfer of petroleum products with aromatic content up to %50

										
	ID	OD		WP	BP		W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft	
MO-020-051-ATT	2	2,48	63	300	900	1750	1,18	300	100	
MO-020-063-ATT	2 1/2	2,99	76	300	900	2570	1,7	380	100	
MO-020-076-ATT	3	3,54	90	300	900	2990	2,01	460	100	
MO-020-102-ATT	4	4,65	118	300	900	4600	3,1	600	100	
MO-020-127-ATT	5	5,71	145	300	900	6700	4,5	750	100	
MO-020-152-ATT	6	6,69	172	300	900	8350	5,6	1000	100	
MO-020-203-ATT	8	8,86	225	300	900	13250	8,9	1200	50	

