

BULK MATERIAL - PARA DISCHARGE HOSE W.P. 150 PSI



Our BULK MATERIAL - PARA DISCHARGE HOSE W.P. 150 PSI is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive beige PARA.

Reinforcement: High-tensile synthetic cord with antistatic copper wire.





Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +70°C (-22°F to +158°F)

Remarks: Upon request heavy version 17 bar (250 ppm) available, also suitable for offshore industry.

Application:

Used for delivery of dry powder, dust and abrasives.

								
	ID	OD		WP	BP	W		L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-010-025-V	1	1,45	37	150	450	645	0,43	100
MM-010-032-V	1 1/4	1,73	44	150	450	850	0,57	100
MM-010-038-V	1 1/2	2,04	52	150	450	1200	0,80	100
MM-010-051-V	2	2,55	65	150	450	1480	0,99	100
MM-010-063-V	2 1/2	3,07	78	150	450	1950	1,30	100
MM-010-076-V	3	3,66	93	150	450	2650	1,78	100
MM-010-102-V	4	4,80	122	150	450	4420	2,97	100
MM-010-127-V	5	5,86	149	150	450	6300	4,23	100
MM-010-152-V	6	6,85	174	150	450	7700	5,17	100



BULK MATERIAL - PARA DISCHARGE HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com