

CHEMICAL EPDM SUCTION & DISCHARGE HOSE W.P. 150 PSI



Our EPDM Chemical Suction and Discharge Hose is engineered for reliability in chemical and acids applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Chemical resistant smooth black EPDM.




Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wires.

Cover: Weather, ozone and abrasion resistant, smooth, cloth impression black EPDM.

Temperature Range: -30°C to +100°C
(-22°F to +212°F)

Applications :

Ideal for use suction and discharge of chemicals and acids

									
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MX-010-019-AE	3/4	1,22	31	150	600	660	0,44	120	100
MX-010-025-AE	1	1,45	37	150	600	800	0,53	150	100
MX-010-032-aE	1 1/4	1,73	44	150	600	1050	0,70	200	100
MX-010-038-AE	1 1/2	2,00	51	150	600	1320	0,88	230	100
MX-010-051-AE	2	2,55	65	150	600	1850	1,24	300	100
MX-010-063-AE	2 1/2	3,09	78	150	600	2640	1,77	380	100
MX-010-076-AE	3	3,62	92	150	600	3200	2,15	450	100
MX-010-102-AE	4	4,64	118	150	600	4200	2,82	600	100



CHEMICAL EPDM SUCTION & DISCHARGE HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com