

CHEMICAL UHMPWE SUCTION & DISCHARGE HOSE

W.P. 250 PSI 250 F



Our High Pressure UPE Chemical Suction and Discharge Hose is engineered for reliability in chemical and acids applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Chemical and solvent resistant white UHMWPE

Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wire.



Cover: Weather, ozone and abrasion resistant, smooth, cloth impression green EPDM.

Temperature Range: -30°C to +80°C (-22°F to +176°F)

Remarks: Upon request other colours available.

Application:

Used for high pressure suction and discharge of chemicals, acids and high aromatic solvents.

									
	ID	OD		WP	BP	W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MX-016-019-AU	3/4	1,22	31	250	1000	630	0,42	120	100
MX-016-025-AU	1	1,45	37	250	1000	780	0,52	150	100
MX-016-032-AU	1 1/4	1,73	44	250	1000	1000	0,67	200	100
MX-016-038-AU	1 1/2	2,00	51	250	1000	1250	0,83	230	100
MX-016-051-AU	2	2,56	65	250	1000	1830	1,22	300	100
MX-016-063-AU	2 1/2	3,08	78	250	1000	2400	1,61	380	100
MX-016-076-AU	3	3,62	92	250	1000	3000	2,01	460	100
MX-016-102-AU	4	4,64	118	250	1000	3900	2,62	600	100



CHEMICAL UHMPWE SUCTION & DISCHARGE HOSE W.P. 250



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com