

CHEMICAL XLPE SUCTION & DISCHARGE HOSE 200 PSI



Our XLPE Chemical Suction and Discharge Hose is engineered for reliability in chemical and acids applications..

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Chemical resistant smooth white XLPE.






Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wire.

Cover: Weather, ozone and abrasion resistant, smooth, cloth impression blue EPDM.

Temperature Range: -30°C to +80°C (-22°F to +176°F)

Application:

Used for suction and discharge of chemicals and acids.

									
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MX-016-019-AX	3/4	1,22	31	200	800	630	0,42	120	100
MX-016-025-AX	1	1,45	37	200	800	780	0,52	150	100
MX-016-032-AX	1 1/4	1,73	44	200	800	1000	0,67	200	100
MX-016-038-AX	1 1/2	2,00	51	200	800	1250	0,83	230	100
MX-016-051-AX	2	2,56	65	200	800	1830	1,22	300	100
MX-016-063-AX	2 1/2	3,08	78	200	800	2400	1,61	380	100
MX-016-076-AX	3	3,62	92	200	800	3000	2,01	460	100
MX-016-102-AX	4	4,64	118	200	800	3900	2,62	600	100



CHEMICAL EPDM SUCTION & DISCHARGE HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com