

CONCRETE PLACEMENT HOSE - STEEL W.P. 1233 PSI



Our Concrete placement hose-steel is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant black NR

Reinforcement: High-tensile steel cords.

Cover: Weather, ozone resistant, abrasion




resistant, cloth impression black SBR

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Remarks: Standart DIN 53516, below: 50 mm3

Application:

Used for high pressure concrete pumping applications.

									
	ID	OD		WP	BP		W	L	
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft	
MM-085-051-A	2	2,79	71	1233	2900	3100	2,08	275	100
MM-085-063-A	2 1/2	3,35	85	1233	2900	4500	3,02	300	100
MM-085-076-A	3	3,94	100	1233	2900	5500	3,69	350	100
MM-085-102-A	4	4,96	126	1233	2900	8500	5,71	400	100
MM-085-127-A	5	6,10	155	1233	2900	9700	6,51	500	100
MM-085-152-A	6	7,09	180	1233	2900	11200	7,52	700	50



CONCRETE PLACEMENT HOSE - STEEL - W.P. 1233 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com