

CONCRETE PLACEMENT HOSE - TEXTILE W.P. 1233 PSI



Our Concrete placement hose-textile is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant black NR

Reinforcement: High-tensile textile cords




Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Remarks: Standart DIN 53516, below: 50 mm³

Application:

Used for high pressure concrete pumping applications.

								
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-085-025-AC	1	1,65	42	1233	2900	1100	0,73	100
MM-085-032-AC	1 1/4	1,89	48	1233	2900	1250	0,83	100
MM-085-038-AC	1 1/2	2,28	58	1233	2900	1950	1,31	100
MM-085-051-AC	2	2,83	72	1233	2900	2500	1,67	100
MM-085-063-AC	2 1/2	3,39	86	1233	2900	3150	2,11	100
MM-085-076-AC	3	3,90	99	1233	2900	3700	2,48	100
MM-085-102-AC	4	4,96	126	1233	2900	4750	3,19	100
MM-085-127-AC	5	6,02	153	1233	2900	6400	4,30	100



CONCRETE PLACEMENT HOSE - TEXTILE - W.P. 1233 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com