

CORRUGATED BULK MATERIAL SUCTION & DISCHARGE HOSE W.P. 150 PSI



Our Corr Bulk Material Suction & Discharge Hose is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR.





Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wire.

Cover: Weather, ozone resistant, abrasion resistant, corrugated, cloth impression black SBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Application:

Used for suction and discharge of dry powder, dust and abrasives.

									
	ID	OD		WP	BP		W	BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MM-010-025-AC	1	1,53	39	150	450	900	0,60	100	100
MM-010-032-AC	1 1/4	1,77	45	150	450	1075	0,72	125	100
MM-010-038-AC	1 1/2	2,04	52	150	450	1375	0,92	150	100
MM-010-051-AC	2	2,59	66	150	450	1925	1,29	200	100
MM-010-063-AC	2 1/2	3,07	78	150	450	2300	1,54	250	100
MM-010-076-AC	3	3,62	92	150	450	3000	2,01	300	100
MM-010-102-AC	4	4,72	120	150	450	4300	2,88	400	100
MM-010-127-AC	5	5,86	149	150	450	6400	4,30	500	100
MM-010-152-AC	6	6,85	174	150	450	8900	5,98	600	100



CORRUGATED BULK MATERIAL SUCTION & DELIVERY HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com