

CORRUGATED CHEMICAL UHMPWE SUCTION & DISCHARGE HOSE W.P. 250 PSI 250 F



Our Corrugated High Pressure Corrugated UPE Chemical Hose is engineered for reliability in chemical and acids applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: Chemical and solvent resistant conductive white UHMWPE.





Reinforcement: High-tensile synthetic cord with wire helix and copper wire.

Cover: Weather, ozone and abrasion resistant, corrugated, cloth impression conductive green EPDM.

Temperature Range: -30°C to +80°C
(-22°F to +176°F)

Application:

Used for high pressure suction and discharge of chemicals, acids and high aromatic solvents.

									
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MX-016-019-CU	3/4	1,22	31	250	1000	630	0,42	100	100
MX-016-025-CU	1	1,45	37	250	1000	780	0,52	125	100
MX-016-032-CU	1 1/4	1,73	44	250	1000	1000	0,67	150	100
MX-016-038-CU	1 1/2	2,00	51	250	1000	1250	0,83	200	100
MX-016-051-CU	2	2,56	65	250	1000	1830	1,22	250	100
MX-016-063-CU	2 1/2	3,08	78	250	1000	2400	1,61	300	100
MX-016-076-CU	3	3,62	92	250	1000	3000	2,01	400	100
MX-016-102-CU	4	4,64	118	250	1000	3900	2,62	550	100



CORRUGATED CHEMICAL UHMPWE SUCTION & DISCHARGE HOSE W.P. 250



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com