

DRY BULK MATERIAL DISCHARGE HOSE W.P. 150 PSI

1/4" TUBE



Our Dry Bulk Hose is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR.

Reinforcement: High-tensile synthetic cord with antistatic copper wire.




Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Remarks: Upon request 8", 10", 12" available

Application:

Used for delivery of dry powder, slurry and cement.

								
	ID	OD		WP	BP	W	L	
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-010-025-V	1	1,45	37	150	450	645	0,43	100
MM-010-032-V	1 1/4	1,73	44	150	450	850	0,57	100
MM-010-038-V	1 1/2	2,04	52	150	450	1200	0,80	100
MM-010-051-V	2	2,55	65	150	450	1480	0,99	100
MM-010-063-V	2 1/2	3,07	78	150	450	1950	1,30	100
MM-010-076-V	3	3,66	93	150	450	2650	1,78	100
MM-010-102-V	4	4,80	122	150	450	4420	2,97	100
MM-010-127-V	5	5,86	149	150	450	6300	4,23	100
MM-010-152-V	6	6,85	174	150	450	7700	5,17	100



DRY BULK MATERIAL DISCHARGE HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com