

DRY BULK MATERIAL SUCTION & DISCHARGE HOSE W.P. 150 PSI



Our Dry Bulk/SD Hose is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR.





Reinforcement: High-tensile synthetic cord with wire helix and antistatic copper wire.

Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Application:

Used for suction and discharge of dry powder, dust and abrasives.

									
	ID	OD		WP	BP	W		BR	L
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	mm	ft
MM-010-025-A	1	1,54	39	150	450	900	0,60	150	100
MM-010-032-A	1 1/4	1,77	45	150	450	1075	0,72	190	100
MM-010-038-A	1 1/2	2,05	52	150	450	1500	1,00	230	100
MM-010-051-A	2	2,60	66	150	450	2000	1,34	300	100
MM-010-063-A	2 1/2	3,14	80	150	450	2980	2,00	380	100
MM-010-076-A	3	3,70	94	150	450	4050	2,72	460	100
MM-010-102-A	4	4,80	122	150	450	5200	3,49	600	100
MM-010-127-A	5	5,87	149	150	450	6900	4,63	750	100
MM-010-152-A	6	6,85	174	150	450	8800	5,91	900	100



DRY BULK MATERIAL SUCTION & DISCHARGE HOSE W.P. 150 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com