

FLAT CEMENT HOSE 75 PSI



Our Flat Cement Hose is engineered for long term strength abrasive, plaster, cement applications

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR.





Reinforcement: High-tensile synthetic cord and antistatic copper wire.

Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Application:

Used for suction and discharge of dry powder, dust ,abrasives and silos.

								
	ID	OD		WP	BP	W	L	
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-005-051-V	2	2,40	61	75	225	1150	0,77	100
MM-005-063-V	2 1/2	2,87	73	75	225	1400	0,94	100
MM-005-076-V	3	3,39	86	75	225	1700	1,14	100
MM-005-102-V	4	4,41	112	75	225	2300	1,54	100
MM-005-127-V	5	5,39	137	75	225	2750	1,84	100
MM-005-152-V	6	6,38	162	75	225	3250	2,18	100
MM-005-203-V	8	8,46	215	75	225	5200	3,49	50
MM-005-254-V	10	10,55	268	75	225	7600	5,10	50
MM-010-152-V	6	6,85	174	150	450	7700	5,17	100



FLAT CEMENT HOSE 75 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040

+1 832 577 2505



info@arkhoses.com