

PARA SLEEVES





Our SLEEVE is engineered for long term strength abrasive, plaster, cement applications. Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Construction: High abrasion resistant

conductive beige colour Natural Rubber
Temperature Range: -30°C to +70°C
(-22°F to +158°F)

Application:

Used for discharge of abrasive materials , dry cements, sand, gravel, cement, grain without pressure

						
	ID	OD		W		L
code	inch	inch	mm	gr/mt	lbs/ft	ft
MM-000-025-PS	1	1,29	33	475	0,31	100
MM-000-032-PS	1 1/4	1,57	40	600	0,40	100
MM-000-038-PS	1 1/2	1,81	46	700	0,47	100
MM-000-051-PS	2	2,32	59	910	0,61	100
MM-000-063-PS	2 1/2	2,79	71	1110	0,74	100
MM-000-076-PS	3	3,30	84	1330	0,89	100
MM-000-102-PS	4	4,33	110	1760	1,18	100
MM-000-114-PS	4 1/2	4,80	122	1960	1,31	100
MM-000-127-PS	5	5,31	135	2170	1,45	100
MM-000-152-PS	6	6,29	160	2600	1,74	100
MM-000-168-PS	6 1/2	6,92	176	2850	1,91	100
MM-000-203-PS	8	8,30	211	3450	2,31	50
MM-000-223-PS	9	9,09	231	3760	2,52	50
MM-000-254-PS	10	10,30	262	4280	2,87	50
MM-000-273-PS	11	11,06	281	4590	3,08	50
MM-000-305-PS	12	12,32	313	5120	3,44	50
MM-000-330-PS	13	13,30	338	5540	3,72	50
MM-000-354-PS	14	14,20	362	5950	3,99	50
MM-000-508-PS	20	20,30	516	8500	5,71	50
MM-000-612-PS	24	24,40	620	10215	6,86	50



PARA SLEEVES



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com