

PLASTER/GROUTING HOSE W.P. 600 PSI



Our Plaster Grouting hose is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR

Reinforcement: High-tensile synthetic cord with antistatic copper wire.





Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +85°C
(-22°F to +185°F)

Remarks: Standart DIN 53516, below: 50 mm³

Application:

Used for Plaster / Grouting services.

								
	ID	OD		WP	BP	W	L	
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-040-025-V	1	1,53	39	600	1800	930	0,62	100
MM-040-032-V	1 1/4	1,81	46	600	1800	1130	0,75	100
MM-040-035-V	1 3/8	2,00	51	600	1800	1250	0,83	100
MM-040-038-V	1 1/2	2,04	52	600	1800	1370	0,92	100
MM-040-051-V	2	2,67	68	600	1800	1800	1,20	100
MM-040-063-V	2 1/2	3,26	83	600	1800	2650	1,78	100
MM-040-076-V	3	3,77	96	600	1800	3400	2,28	100
MM-040-102-V	4	4,80	122	600	1800	4250	2,85	100
MM-040-127-V	5	6,10	155	600	1800	7100	4,77	100
MM-040-152-V	6	7,08	180	600	1800	9900	6,65	100



PLASTER/GROUTING HOSE W.P. 600 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com