

PLASTER/GROUTING HOSE W.P. 800 PSI



Our Plaster Grouting Hose is engineered for long term strength abrasive, plaster, cement applications.

Designed with superior materials, it offers excellent resistance to abrasion, weather, and ozone, ensuring long-lasting performance across industrial settings.

Tube: High abrasion resistant conductive black NR.

Reinforcement: High-tensile synthetic cord with antistatic copper wire.




Cover: Weather, ozone resistant, abrasion resistant, cloth impression black SBR.

Temperature Range: -30°C to +85°C
(-22°F to +185°F)

Remarks: Standart DIN 53516, below: 50 mm³

Application:

Used for Plaster / Grouting services.

								
	ID	OD		WP	BP	W	L	
code	inch	inch	mm	psi	psi	gr/mt	lbs/ft	ft
MM-055-025-V	1	1,53	39	800	2400	940	0,63	100
MM-055-032-V	1 1/4	1,81	46	800	2400	1150	0,77	100
MM-055-038-V	1 1/2	2,04	52	800	2400	1390	0,93	100
MM-055-051-V	2	2,71	69	800	2400	1900	1,27	100
MM-055-063-V	2 1/2	3,26	83	800	2400	2700	1,81	100
MM-055-076-V	3	3,77	96	800	2400	3500	2,35	100
MM-055-102-V	4	4,96	126	800	2400	4300	2,88	100



PLASTER/GROUTING HOSE W.P. 800 PSI



www.arkhoses.com



13201 NW Freeway, Suite 800,
Houston, Texas, 77040
+1 832 577 2505



info@arkhoses.com